


GREPP

EX™




- 1. EX™ - CTL
- 2. Normal
- 3. 22 och 26 mm
- 4. Narrow och Standard
- 5. SYM
- 6. NC, SC och DC

774-960 mm bred



OF™




- 1. OF™ - CTL
- 2. Normal
- 3. 22 och 26 mm
- 4. Narrow, Standard och Soft
- 5. SYM
- 6. NC, SC och DC

655-906 mm bred



EVO™



- 1. EVO™ - CTL
- 2. Light och Normal
- 3. 22 och 26 mm
- 4. Narrow, Standard och Soft
- 5. SYM
- 6. NC, SC och DC

695-960 mm bred



ALLROUND

ECO™



- 1. ECO™ - CTL
- 2. Normal
- 3. 22 och 26 mm
- 4. Narrow, Standard och Soft
- 5. SYM
- 6. NC, SC och DC

615-944 mm bred



KovaX™



- 1. KovaX™ - CTL
- 2. Normal och Plus
- 3. 22 och 26 mm
- 4. Narrow, Standard och Soft
- 5. SYM och OSS
- 6. NC, SC och DC

680-950 mm bred



Baltic™



- 1. Baltic™ - CTL
- 2. Light och Normal
- 3. 22 och 26 mm
- 4. Narrow, Standard och Soft
- 5. SYM, ASYM och OSS
- 6. NC, SC, DC och RC

650-1210 mm bred



BÄRIGHET

Skidder Wheel Tracks™

